

# OLDROYD 'Xs' FlooringMembrane



Allows **fast-track** installation of **floor finishes** over newly laid floor-slabs and **damp and contaminated** floors.



## Description

Oldroyd Xs is a tough, damp-proofing membrane that can be laid on top of damp concrete floors or newly laid floor-slabs. A wide choice of flooring types can then be laid on top, for example, screeds, particle board, and laminated wooden flooring. Insulation can also be used in conjunction with the system, where required.

Oldroyd Xs is much thicker than conventional damp-proofing membranes, and is manufactured from polypropylene – making

it extremely strong and resistant to damage.

The patented "X" pattern embossed into the membrane makes it easy to cut and fold. It also allows moisture to move behind the membrane, and allows for shrinkage movement when screeds are laid on top.

## Advantages

In refurbishment projects, Oldroyd Xs can allow new finishes to be applied to existing floors without the need to resort to expensive excavation and relaying of damp floors. Oldroyd Xs protects the flooring finish from dampness as well as contaminants such as oil, gas, and acids, making it an excellent choice for factory and warehouse conversions.

Where new floor slabs are to be laid, the use of Oldroyd Xs can allow the fast-track installation of floor finishes while the floor slab is still "drying down," allowing faster completion of projects.



# OLDROYD

THE ULTIMATE WATERPROOF MEMBRANE SYSTEM

# OLDROYD 'Xs' Flooring Membrane



## Application

Oldroyd Xs can be laid directly onto floors with minimal preparation. Where rolls of Oldroyd Xs need to be joined, Oldroyd double-sided sealing tape should be used. Where the membrane meets walls, it should be allowed to lap 100mm up the wall.

Full application guidelines can be downloaded from [www.safeguardchem.com](http://www.safeguardchem.com)

## Aggressive Groundwater

Oldroyd Xs Flooring Membrane should not be used in aggressive groundwater situations. The studded Oldroyd Xv membrane should be used instead. Call our technical department for details.

## Availability

Oldroyd Xs is available in rolls of the following sizes:

1.28 x 20m (25.6m<sup>2</sup>)  
2.08 x 20m (41.6m<sup>2</sup>)



## Further Reading

Further information about Oldroyd 'Xs' Flooring Membrane can be found in the following publications:

Oldroyd Exterior Walls

Oldroyd Flooring

These publications can be downloaded free-of-charge from [www.safeguardchem.com](http://www.safeguardchem.com)



Oldroyd Membranes are distributed in the UK by:



Safeguard Chemicals  
Redkiln Close, Horsham,  
West Sussex, RH13 5QL.  
Tel: 01403 210204  
Fax: 01403 217529  
Web: [www.safeguardchem.com](http://www.safeguardchem.com).  
E-mail: [info@safeguardchem.com](mailto:info@safeguardchem.com)